

CRD - 4" & 6" Cleanroom Downlights

Illuminating Precision Spaces

Certolux's specification-grade cleanroom downlights, are carefully engineered to provide laboratory illumination from a sealed, smooth and cleanable aperture. These fixtures feature an option for 97+ CRI, with very high R9 value, providing improved color recognition.

CRD downlights are certified NSF2 and carry an ISO3 cleanroom rating. The CRD series can emit up to 5000 lumens and provide full-range dimming to 1%. This provides the flexibility that laboratory staff need, allowing them to adjust the lighting to their specific requirements. The low cutoff angle reduces glare reflected on monitors and glossy surfaces. These gasketed flush lensed luminaires are designed to seal the ceiling and prevent the entrance of contaminated air into the cleanroom.

Discover the power of Certolux's CRD downlights and see how they meet stringent cleanroom standards.

Features Options:

- Designed for use with Grid, Drywall or Cleanroom Panel Ceilings up to 2.5" thick
- Delivered lumens: 1000 - 5,100 lm
- Standard smooth wipe-down flush lens
- ISO 60598 IP65 Certified
- NSF2 Splash Zone Certified
- Antimicrobial finished trims
- Amazing glare control with UGR as low as 11



4-inch



6-inch



Shown here is a 6" downlight