

										
Model	LMEZ-Micro	LMEZ 2	LMEZ 3 SQUARE	LMEZ 3	LMEZ	LMEZX Multi-Function	LMEZY Multi-Function	ALRA	ALRB	ALRM
Grade	Premium	Premium	Premium	Premium	Specification	Specification	Specification	Premium	Premium	Premium
Cost	\$\$	\$\$	\$\$	\$\$	\$\$\$	\$\$\$	\$\$\$	\$\$	\$\$	\$\$
Installation	Suspended	Suspended / Continuous Run	Suspended / Continuous Run	Suspended / Continuous Run	Surface / Suspended / Pendant / Wall / Continuous Run	Surface / Suspended / Pendant / Wall / Continuous Run	Recessed / Continuous Row	Suspended	Suspended	Suspended
Lengths	48" / 96"	24" / 48" / 72" / 96"	24" / 48" / 72" / 96"	24" / 48" / 72" / 96"	24" / 48" / 96"	24" / 48" / 96" / 144"	24" / 48" / 96" / 144"	48" / 96"	48" / 96"	48" / 96"
Width x Height	1½" x 2½"	2" x 4"	3" x 3"	3" x 4½"	6" x 6"	3" x 4½"	3" x 4½"	6½" x 2"	6½" x 2½"	6½" x 2½"
Lens	Frosted Acrylic	Frosted Acrylic	Frosted Acrylic	Frosted Acrylic	Clear Prismatic #12 Acrylic	Top: Clear Acrylic Bottom: Frosted Acrylic	Frosted Acrylic	Frosted Acrylic	Frosted Acrylic	Frosted Acrylic
Light Distribution	Direct	Direct	Direct	Direct Indirect / Direct	Indirect / Direct	Direct Indirect / Direct	Direct	Indirect (50%) / Direct (50%)	Indirect (25%) / Direct (75%)	Indirect (25%) / Direct (75%)
Standard Dimming	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)	0-10V (1%)
Lumen Packages	Down: 400 - 1,000 lm/ft	Down: 400 - 1,000 lm/ft	Down: 400 - 1,500 lm/ft	Up: 280 - 600 lm/ft Down: 400 - 1,500 lm/ft	Up: 250 lm/ft Down: 1,250 lm/ft	Up: 275 lm/ft Down: 275 lm/ft	Down: 550 lm/ft	Up: 437 - 750 lm/ft Down: 437 - 750 lm/ft	Up: 437 - 750 lm/ft Down: 437 - 750 lm/ft	Up: 200 - 375 lm/ft Down: 600 - 1,125 lm/ft
System Watts	4 - 11 w/ft	8.5 - 22.5 w/ft	3.4 - 12.8 w/ft	7 - 30 w/ft	8.5 - 19 w/ft	5.5 w/ft	5.5 w/ft	6.5 - 11.75 w/ft	6.5 - 11.75 w/ft	6 - 11.25 w/ft
Notable Options	Custom Lumen Packages Tunable White (2700-6500K) Straight Blade Louvers (White, Silver Grey, Black) Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages Tunable White (2700-6500K) EM Battery Pack Straight Blade Louvers (White, Silver Grey) Lens Options: Regressed / Black Acrylic Bottom Lens / Inverted-V / Drop Lens Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages Tunable White (2700-6500K) EM Battery Pack Straight Blade Louvers (White, Silver Grey) Lens Options: Regressed / Black Acrylic Bottom Lens / Inverted-V / Drop Lens Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages Tunable White (2700-6500K) EM Battery Pack Straight Blade Louvers (White, Silver Grey) Lens Options: Regressed / Black Acrylic Bottom Lens / Inverted-V / Drop Lens Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages EM Battery Pack Baffle Options: Parabolic Blade Semi-Specular, Straight Blade White Lenses: Smooth Opal Acrylic, White Translucent Acrylic Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages EM Battery Pack Baffle Options: Parabolic Blade Semi-Specular, Straight Blade White Lenses: Smooth Opal Acrylic, White Translucent Acrylic Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages EM Battery Pack Trim Options: Flanged / Flangeless Wiring Options	Custom Lumen Packages Tunable White (2700-6500K) EM Battery Pack Corners, T-Connectors, Cross-Connectors for shape creation. Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages Tunable White (2700-6500K) EM Battery Pack Corners, T-Connectors, Cross-Connectors for shape creation. Power Cord Options Sloped Ceiling Mounting	Custom Lumen Packages Tunable White (2700-6500K) EM Battery Pack Light Distribution Options Lens Shape Options Corners, T-Connectors, Cross-Connectors for shape creation. Power Cord Options Sloped Ceiling Mounting

Universal to all Linear Lighting products:

Driver Options	Bi-Level (50/100) DALI/1%
CCT	3,000K - 5,000K
CRI Available	80+ / 90+
Color Finishes	White, Black, Silver Grey. Custom colors also available. Consult factory
L80 Performance	> 50,000hrs
Voltage	UNV / 347V
Ratings	Suitable for Damp Locations
Control Types	Wireless Controls

