

General Lighting Fixtures with Integrated Controls

ALLURA A



Description

Leviton General Lighting Fixtures with Integrated Controls are self-contained, fully integrated fixtures for commercial LED solutions. The LED ALLURA Linear Pendant Type A (ALRA) is a bidirectional, pendant mount luminaire featuring an architectural slim profile with soft curves to enhance the visual space. This pendant-mount luminaire comes with a double tear drop shaped frosted diffuser that offers a high level of efficiency and visual comfort.


This luminaire features the Solo standalone occupancy sensor with daylight harvesting or the Intellect™ wireless occupancy/daylight sensor* that integrates into the GreenMAX® DRC Wireless system lighting control system.

Applications

- Boardrooms
- Corridors
- Retail stores and supermarkets
- Studio lofts
- Offices

*Available through a Leviton Agent only.


Mounting Points




Features

- Double teardrop extruded diffusers
- Emergency lighting battery pack
- Two integrated control options available
- Standard low voltage dimming (0-10V)
- UL, cUL listed
- 5-year limited warranty

Dimensions



Top View




End View

Size (Nominal Length)	A	B	C
48	45"	6.50"	2"
96	89"	6.50"	2"

Consult installation guide for exact dimensions.

Photometrics

ES File: ALRA48-LED840K60LUNV
umens: 5928
Voltage: 47
Efficacy: 126



Zonal Lumen Summary

Zone	Lumens	%Fixture
0.0° - 30.0°	412	7.0%
0.0° - 40.0°	723	12.2%
0.0° - 60.0°	1558	26.3%
0.0° - 90.0°	3031	51.1%
0.0° - 110.0°	3985	67.2%
0.0° - 130.0°	4873	82.2%
0.0° - 150.0°	5534	93.4%
0.0° - 170.0°	5883	99.2%
0.0° - 180.0°	5928	100.0%

Coefficients of Utilization

pc	80%	70%	50%
0	107 107 107	99 99 99	84 84 84
1	94 88 82	86 81 76	72 68 64
2	84 75 67	77 68 62	63 57 52
3	76 64 55	69 59 51	57 49 43
4	69 56 47	63 52 43	51 43 36
5	63 49 40	57 45 37	47 38 31
6	58 44 35	52 40 32	43 34 27
7	53 39 31	48 36 28	40 30 24
8	49 36 27	45 33 25	37 28 21
9	46 32 24	42 30 22	34 25 19
10	42 30 22	39 27 20	32 23 17

Average Luminance Table (cd/m²)

CP Summary	0.00°	45.00°	90.00°
0.00°	2557	2557	2557
45.00°	2742	3276	4130
55.00°	2726	3796	5470
65.00°	2627	4610	7609
75.00°	2390	6157	11347
85.00°	1479	10408	20033

Effective Floor Cavity Reflectance: 20%

Leviton Manufacturing Co., Inc. Lighting & Controls

10385 SW Avery Street, Tualatin, OR 97062 tel 800-736-6682 tech line (6:00AM-4:00PM PT Mon-Fri) 800-959-6004

©2023 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.


Product Data

General Lighting Fixtures— ALRA




Specifications

Lifetime Rating	Long life LEDs coupled with high efficiency drivers provide quality illumination; rated to deliver L80 performance > 50,000 hours
Optical System	Frosted acrylic diffuser offer high levels of efficiency and visual comfort; the bidirectional optics provide a wide, uniform light distribution; standard distribution is 50% up and 50% down
Mounting	Single-point aircraft cable mounting system used at each hanging location
Construction	Precision-formed steel housing assembly
Finish	Polyester powder painted finish (textured matte white)
Listings	UL, cUL
Warranty	Limited 5-year


Ordering Key



Suspension Kits and Power Feeds (Sold separately)

Cat. No.	Description
KIT00-188	 48" Aircraft Cable and Canopy
KIT00-189	 5-Wire Universal Power Feed with 48" Aircraft Cable and Canopy
KIT00-230	 6-Wire Universal Power Feed with 48" Aircraft Cable and Canopy (Emergency)

Wireless Controls (Sold separately)



Cat. No.	Description	Sensor Type Compatibility
DRKDN-U1W*	1 Button Keypad	V99(LV01)
DRKDN-U2W*	2 Button Keypad	
DRKDN-U4W*	4 Button Keypad	
DRKDN-U8W*	8 Button Keypad	
ZLS0R-RA1	Remote Controller	V99(LV02)

*Available through a Leviton Agent only.

Leviton Manufacturing Co., Inc. Lighting & Controls

10385 SW Avery Street, Tualatin, OR 97062 tel 800-736-6682 tech line (6:00AM-4:00PM PT Mon-Fri) 800-959-6004
©2023 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

LES-G-10565A/123-aa
REV SEP 2023