

# VRSE-5 / VRSD-5

## The Unbreakable Luminaires

Certolux's VRSE-5 and VRSD-5 are truly unbreakable luminaires. These highly durable LED architectural luminaires are of specification-grade construction and suited for high abuse applications. The housing is constructed from extruded aluminum with 2 die-cast end plates options. The polycarbonate lens and tamper resistant fasteners allow this unit to withstand high impact areas.

The VRSE-5 can be ceiling or wall mounted and is suitable for wet locations (ceiling mount) and damp locations (wall mount). The VRSD-5 is a pendant/surface mount luminaire appropriate for damp locations only. It is ideal for high traffic and abusive applications such as educational facilities, locker rooms, community centers, restrooms, stairwells and other public spaces. Both luminaires have an operating ambient temperature range as low as -30°C to as high as 40°C.

### Highlights:

- Fully illuminated appearance
- Durable 0.160 thick opal polycarbonate lens
- Continuous Row mounting options
- Ready for surface conduit connections
- Sealed for long-life

### Features:

- Die-cast endcaps (Rounded and Flat)
- Extruded aluminum housing
- Standard low voltage dimming (0-10v)
- ADA compliant design



### To learn more about both luminaires:

VRSE-5 Wet and Damp Location, [click here](#)

VRSD-5 Damp Location, [click here](#)



Die Cast Endcap  
Rounded



Die Cast Endcap  
Flat



Both luminaires can  
be row-mounted

The VRSE-5 and VRSD-5 is Available in 2, 3, 4, 6 and 8 foot assemblies.