










Product Name	Grade	In-Field Serviceable	Servicing Access Point	Standard Lens	Additional Lens Options	Standard Sizes	Custom Lumen Packages	Lighting Technology	Driver & Dimming	Performance	Stand-Alone Sensor Options	Wireless Networked Control Options
LRTL 	Commerical	✓	Room-Side (LED Module) Plenum-Side (Driver)	Flat Pressure-Fitted Polycarbonate — 5.3" — 	—	1x4 2x2 2x4	—	Static White (standard)	0-10V, 10% (standard)	130 - 141 Lm/W  Pending	Limited (consult factory)	—
LRTH 	Commercial	✓	Room-Side	Formed Frosted Acrylic — 2.9" — 	✓	1x4 2x2 2x4 30x30 750x750 20x60 500x1500	✓	Static White (standard) • Tunable White • BIOS (optional)	0-10V, 10% (standard) • 0-10V, 1% • 0-10V, 0.1% • DALI (optional)	143 - 156 Lm/W 	✓	✓
LRTF 	Specification	✓	Room-Side	Formed Frosted Linear Ribbed Acrylic — 4.6" — 	✓	1x1 1x4 2x2 2x4 30x30 750x750 20x60 500x1500	✓	Static White (standard) • Tunable White • BIOS (optional)	0-10V, 1% (standard) • 0-10V, 0.1% • DALI (optional)	144 - 159 Lm/W 	✓	✓