

MD3G-4103

LED - Recessed Grid Medical Patient Reading/Ambient/Exam

Project:	Catalogue #:	Type:
Notes:		

Product Description

The MD3 series by Certolux is an IC-rated, IP65 (optional), specification-grade luminaire which provides a cost-effective LED patient room lighting solution. Designed as a combination Reading/Ambient/Exam light for hospitals, nursing homes and other patient care facilities. Eliminates the need for wall mounted luminaires. The flexibility of the nominal 2' x 4' singular modular installation makes this an excellent ceiling-mount fixture. For use in insulated ceilings.

Feature Options

- Emergency Battery Pack
- Shielding Perforated Lens
- Radio Frequency Filter
- Low Voltage Controller



Housing

Precision formed, code gauge cold rolled steel. Wiring access plate or knockouts are provided on back of housing, for flexible conduit attachment.

Mounting

Holes provided for chain mounting support to building structure, and comes with integral earthquake clips.

Door Frame & Lens

Optional inset single piece door frame with germ shield available. Optional IP65 versions single piece door frame with 0.125" clear acrylic lens available. (See option codes in ordering key).

Multi-Compartment Optics

The reading compartment is protected by a clear acrylic lens. An extruded frosted linear prismatic acrylic lens is used in the ambient compartment. Optional perforated shields can be added for visual comfort (see ordering key). The exam compartment is shielded by an engineered polycarbonate lens.

Finish

The luminaire is powder painted matte white finish and offers a high reflectivity coating for improved lighting performance and efficiency. Anti-microbial finish is also available.

Electrical

Long life LED's coupled with high efficiency drivers provide quality illumination. Rated to deliver an L80 performance >50,000 hours. The standard driver has a THD of <10%. Standard low voltage dimming (0-10v,1%) (dimming not available in exam section). All electrical components are CSA or UL approved. A wire access plate is provided for wiring connections. Optional low voltage controller available for pillow switch operation (pillow switch by others) (see ordering key for options).

Warranty

5 year limited warranty. For complete warranty, click here:




Approvals

- Approved to CSA and UL standards.
- Suitable for Damp Location.
- UL listed for insulated ceilings.
- Optional IP65 rated available (see ordering key).



Dimensions



Dimensions (inch) & Weights			
Mount Type - G	A	B	C
2x4	23.75"	3.25"	47.75"

Consult installation guide for exact dimensions.

MD3G-4103


LED - Recessed Grid Medical Patient Reading/Ambient/Exam

CERTOLUX a **LEVITON** brand

Project:	Catalogue #:	Type:
Notes:		

Order Key

EXAMPLE: MD3G-4103-LED835K016L/034L-940K100LUNV-C84(G)



Performance Data					
Rating		Ambient		Exam	
Nominal Lumens	Watts	Nominal Lumens	Watts	Nominal Lumens	Watt
1600	17	2200	20	7500	65
2200	20	3400	30	10000	90

Construction Options



Lens Options



* 90+ CRI reduces lumen output by 20%, not available with 5000K.

Other options may be available, consult factory.
Specifications and data subject to change without notice.