

Project
Type
Date
Cat #

Application Features

Specification-grade, surface-mounted ceiling luminaire. For use with indoor applications where aesthetics and quality are important.



Specifications

Optical System

Standard diffuser is a clear, prismatic pattern #12, acrylic lens.

Mounting

This product can be surface or stem-mounted.

Construction

Spot-welded for rigidity and clean appearance. Ballast cover snaps into place eliminating the need for tools when accessing the ballast. Diffuser is held within a hinged door frame. The heavy-gauge frame is held in the closed position by two positive cam latches.

Finish

White, polyester powder painted housing.

Electrical

Rotary lampholders ensure positive lamp retention. Sufficient knockouts are provided for connections.

Approvals

Approved to CSA and UL standards.

Features

- Clean appearance - no exposed fasteners
- Shallow design - only 4 inches deep
- Clear prismatic lay-in acrylic diffuser
- Available with 1, 2, 3, 4 or 6 lamps (T5 and T8 configurations)

Options & Adders

- Enhanced specular aluminum reflector with a minimum reflectance of 95%
- Multi-level switching
- Dimmable and Emergency ballast
- Radio interference filter (120V - 277V)
- Regressed aluminum door frame
- 20 gauge heavy-duty construction
- Deep housing
- Light leak gasketing

Applications

- Classrooms
- Corridors
- Hospitals
- Nursing Homes
- Office Areas
- Stairwells

Dimensions



