


Project
Type
Date
Cat #

Application Features

Specification-grade, recessed wall wash luminaire. For use with indoor applications such as in institutions, retail stores and supermarkets where wall-mounted displays or visual information boards require external illumination. This luminaire eliminates cave effect and scalloping.



Specifications

Optical System

Solid white reflectors are standard. Optional reflectors are available in specular aluminum with a minimum reflectance of 95%.

Mounting

Luminaire may be mounted in T-Bar ceilings or in Drywall spaces, individually or in rows (row mounting available in T5 only).

Construction

Die-formed and spot welded, heavy-gauge steel housing assembly. Spot-welded for rigidity and clean appearance. Flattened knockouts are provided on ends for through wiring.

Finish

White, polyester powder painted housing. High-reflectivity coated reflecting surfaces for improved efficiency.

Electrical

Rotary lampholders ensure positive lamp retention. Sufficient knockouts are provided for connections and through wiring.

Approvals

Approved to CSA and UL standards.

Features

- Ideal for lighting chalk boards, white boards or wall mounted displays
- Available with 1 or 2 lamps (T5, T8 and PLL/Biax configurations)
- High reflectance internal reflector

Options & Adders

- Enhanced specular aluminum reflector with a minimum reflectance of 95%
- Dimmable and Emergency ballast
- Radio interference filter (120V - 277V)
- In-line fuse holder

Applications

- Classrooms
- Displays
- Retail Stores and Supermarkets

Dimensions

